

1ST CHOICE
FOR OVER 50 YRS

WORLD'S
LEADING
RESCUE
TOOLS

SETTING THE
NEW STANDARD
**COMBI TOOL
5160**

 **holmatro**
mastering power

UNMATCHED

In Power, Performance and Weight

The new 5160 combi tool is a winner on all counts: highest force, largest spreading distance and biggest cutting opening. Its unique grip tooth on both blades helps to keep wide materials inside the opening for optimal cutting performance. And while this combi tool is built for multiple heavy duty tasks it has the lowest weight in its class.

Part of the new 5000 Series Combi Tools

DESIGNED AROUND YOU

You never know what you're up against out there. The 5160 combi tool gives you ultimate flexibility: a single piece of equipment for cutting, spreading, squeezing and pulling. With its exceptional performance and superior grip this is a tool you can rely on in any situation.



REMOVABLE TIPS

Large spreading distance and cutting opening

Gives you great operational flexibility. Cuts wider materials and creates all the space you need.

Unique grip tooth

For extra bite when cutting. To prevent wider materials from being pushed out of the blades.

Removable spreading tips

To finish a cut without crushing material between the tips. Designed in one piece to prevent losing parts. Quick single-handed removal. With reflective markings for optimal visibility.

i-Bolt

Flat central bolt construction minimizes blade separation and maximizes cutting performance.

LARGE SPREADING DISTANCE AND CUTTING OPENING

GRIP TOOTH



i-Bolt

Ergonomic carrying handle

New battery: 20% more capacity. Work longer on one battery!

Integrated LED lighting

EVO 3 CORDLESS TECHNOLOGY

Also available with CORE technology



THE CHOICE IS YOURS

Same performance, different benefits

Powered by EVO 3 cordless technology or CORE technology



GCT 5160 EVO 3



CT 5160

**WATCH THE VIDEO ON
HOLMATRO.COM/EN/
COMBI – TOOL – 5160**

SPECIFICATIONS AND ACCESSORIES

Specifications		GCT 5160 EVO 3	CT 5160
Article number		150.052.098	150.012.330
Powered by		EVO 3 cordless technology	CORE technology
Max. working pressure	bar/Mpa	720 / 72	720 / 72
Spreading distance	mm	468	468
Max. cutting opening	mm	394	394
Max. spreading force	kN/t	1367 / 139.4	1367 / 139.4
Min. spreading force (EN 13204)	kN/t	44.5 / 4.5	44.5 / 4.5
Max. cutting force	kN/t	929 / 94.7	929 / 94.7
Max. squeezing force	kN/t	87.9 / 9	87.9 / 9
Max. pulling force	kN/t	105 / 10.7	105 / 10.7
Round bar (EN 13204)	mm	40	40
Weight, ready for use	kg	23.3	17.6
Dimensions (LxWxH)	mm	1022 x 276 x 202	885 x 279 x 201
EN 13204 classification		CK45/468J-23.3	CK45/468J-17.6
EN 13204, cutting capacity		1J 2K 3K 4K 5K	1J 2K 3K 4K 5K
NFPA 1936, cutting capacity		A8 B9 C8 D9 E9	A8 B9 C8 D9 E9
Protection rate		IP54	IP68

Accessories	Art. nr.	GCT 5160 EVO 3	CT 5160
Battery BPA286, 6 Ah - 28V	151.000.307	•	
Battery charger BCH1, 220-240V	150.182.208	•	
Battery charger BCH2, 100-120V	150.182.209	•	
Battery car charger BCH3, 12-24 VDC	150.182.286	•	
Mains power connector BMC1, 220-240V *	150.182.206	•	
Mains power connector BMC2, 100-120V *	150.182.207	•	
Greenline battery pouch	150.182.214	•	
Carrying strap	150.182.249	•	
Spreading tips set, STS 04	150.014.731	•	•
Pulling attachments set, PAS 07	150.182.078	•	•
Pulling chains set, PCS 03	150.582.261	•	•
Pulling chains set, PCS 04, in case	150.582.020	•	•
Accessory set, PAC 03, in case	150.182.365	•	•

* Mains cable length: 2.5 m, tool cable length: 8 m



Battery BPA



Battery charger



Mains power connector



Battery pouch



Carrying strap



Spreading tips set



Pulling attachments set



Pulling chains set



Pulling chains set, in case



Accessory set, in case

EXCEPTIONAL
PERFORMANCE
AND SUPERIOR
GRIP

holmatro.com

 Holmatro Rescue World

 @HolmatroRescue

 holmatrorescue

 HolmatroRescue

You can count on us, for life

© Holmatro 0718.03 981.000.004

Disclaimer - While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. N.V. Holmatro and its affiliated companies (here-after: Holmatro) cannot be held liable in any way for the consequences of activities undertaken based on this printed matter. If you have any doubts about the correctness or completeness of the information, please contact Holmatro (phone number: +31 (0)162-589200). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorization of Holmatro.