

TECHNICAL SPECIFICATION SHEET | ACCESSORIES | BCT 4120 / BCU 4010 GP

Battery



150.553.014
24V 2.4 Ah
NiCd
air-cooled
150.553.050
24V 3.0 Ah
NiMH
air-cooled

Chargers



150.553.007
110-120 V AC (2-pin USA)
full recharge in 1 hour
air-cooled
150.553.008
220-230 V AC (2-pin EUR)
full recharge in 1 hour
air-cooled
150.553.009
220-230 V AC (3-pin UK)
full recharge in 1 hour
air-cooled

Inverter 12 VDC - 230 VAC



150.003.772
for use in combination with a 230V
battery charger
enables to charge BCT/U batteries
from a vehicle's 12VDC battery

Auxiliary power cords



150.553.045
12-24 VDC
5 m with crocodile clamps
provides tool with unlimited run time
using a vehicle's power
150.553.052
24 VDC
10 m with crocodile clamps
provides tool with unlimited run time
using a vehicle's power

Carrying / storage case



150.003.381
robust carrying/storage case.
-12.6 kg, LxWxH = 801x522x318mm
- with layered foam interior, pull
handle and wheels
- for 1 tool, 3 batteries, 1 charger, 1
set pulling attachments, 1 set pulling
chains and auxiliary cord

Carrying bag



150.553.054
to carry 1 tool plus 5 batteries
standard excluding the (4) battery
pouches

Pouch



150.553.113
to store 1 battery or pulling chains
can be attached to a belt
made of rugged canvas with Velcro®
straps

Carrying strap



150.553.055
to carry the tool safely
equipped with quick release clamps

Backpack harness



150.553.115
to carry the tool on the back of the
rescuer

Carrying / storage frame



150.553.048
rugged frame to hold 1 tool plus 2
batteries
weight 4.0 kg

Set pulling attachments - BCT only



150.582.551
for 10 mm shackle

Set pulling chains - BCT only



150.582.152
1.5 and 3 m
10 mm shackle