

SPREADERS

5000 series

1ST CHOICE
FOR OVER 50 YRS

WORLD'S
LEADING
RESCUE
TOOLS

Ultra-lightweight*

Spreading tips
with perfect grip

Compact design,
ultra-lightweight

Ergonomic
carrying handle

Six integrated LED lights
with high light output

Built-in
Speed Valve

One hose and coupler thanks
to patented CORE Technology

SP 5240 CL
9.6 kg

Lightweight



SP 5240
14.5 kg



SP 5250
15.9 kg



SP 5260
19.6 kg



SP 5280
19.4 kg

*

The SP 5240 CL has been developed entirely on the basis of the high demands of practical application. This has resulted in a spreader that is even more compact and lightweight than the other- already very light - models from the new 5000 series. Combining ergonomics with performance the SP 5240 CL is everything you need for the extrication of a trapped victim.

The new 5000 series spreaders

Lighter than ever, no concessions

When it comes to the crunch, you can count on Holmatro spreaders. The most important factor in the development of our new 5000 series spreaders was weight reduction. Without compromising quality, spreading force and spreading distance. The result? The new 5000 series is lighter than ever, without concessions. Five spreaders with an optimum performance-to-weight ratio. All models are ergonomically designed, offer ultimate grip and have integrated LED-lighting with high light output. Above all, four models are available with a Greenline battery for increased freedom of movement.



Features & benefits

This is what makes the new 5000 series spreaders so unique*



Ergonomic carrying handle
New ergonomic carrying handle design increases operator comfort in various working positions.



Integrated LED lighting
New LED lighting in the carrying handle: no less than six LED lights with a higher light output. Rescuers can start right away, both during the day and at night, without working in their own shadow.



Lightweight
Lighter than ever thanks to new materials, component integration and smart design. Easy to carry and handle, reducing physical burden.



Patented CORE Technology
CORE Technology combines oil feed and return in one hose and makes operations safer, quicker and easier.



Perfect grip
Perfect grip in every situation and under all circumstances thanks to the well-considered and effective profile of the spreading tips.



Built-in Speed Valve
When unloaded, the arms open quickly to the desired distance to speed up spreader positioning.

*

More than just spreading

The new Holmatro 5000 series spreaders do not just offer the very best in spreading capabilities. Our spreaders are multi-functional. Next to spreading they can also squeeze, and with the help of accessories, pull or cut.

The development of the SP 5240 CL (Compact Lightweight) is a story in itself. Our R&D department was not influenced by international standards such as EN 13204 and NFPA 1936. To completely meet the wishes of the users, the SP 5240 CL was developed entirely on the basis of the high demands of practical application. This has resulted in an exceptional spreader, which is more compact and lightweight than all the other – already very light – models from the new 5000 series. And best of all, which can do all that is required to extricate a trapped victim.

Successfully tested on the latest car models

The SP 5240 CL has been tested extensively on the latest car prototypes and has proved its worth time and time again. It offers every spreading capability you need when dealing with new car construction. We believe this is more important to you than knowing that a product meets all performance requirements of the international standards. However, even though the SP 5240 CL was not designed on the basis of these standards, it fully complies with NFPA 1936 and – except for the spreading distance – with EN 13204.



Holmatro spreader SP 5240 CL

Developed on the basis of practical application



- Weight 9.6 kg
- Relevant spreading force* 40 kN / 4.1 t
- Spreading distance 510 mm

* this is the minimum spreading force you will always have at your disposal, measured at the top of the spreading tips over the full spreading distance

Specifications		SP 5240 CL
article number		150.012.322
equipped with (connector type)		CORE
EN 13204 **		✓
NFPA 1936		✓
max. working pressure	bar/Mpa	720 / 72
spreading distance	mm	510
max. spreading force	kN/t	131 / 13.4
min. spreading force (EN 13204)	kN/t	40 / 4.1
max. spreading force (NFPA 1936, HSF)	kN/t	53 / 5.4
min. spreading force (NFPA 1936, LSF)	kN/t	35 / 3.6
max. squeezing force	kN/t	47 / 4.8
pulling distance	mm	393
max. pulling force	kN/t	47 / 4.8
max. pulling force (NFPA 1936, HPF)	kN/t	47 / 4.8
min. pulling force (NFPA 1936, LPF)	kN/t	24 / 2.4
weight, ready for use	kg	9.6
dimensions (L x W x H)	mm	685 x 274 x 207
required oil content	cc	124
temperature range	°C	-20 – +55
built-in Speed Valve		✓
carrying handle lighting (6 LEDs)		✓

** EN 13204 compliant, except for spreading distance



Accessories		Art. No.
1	pulling attachments, set	150.182.273
2	accessories, set in case (2 spreading tips, 2 pulling attachments)	150.182.289
3	pulling chains, set	150.582.152
4	pulling chains, set in case	150.582.021

Holmatro spreader SP 5240

- Weight 14.5 kg
- Relevant spreading force* 41 kN / 4.2 t
- Spreading distance 725 mm



* this is the minimum spreading force you will always have at your disposal, measured at the top of the spreading tips over the full spreading distance

Specifications		SP 5240
article number		150.012.323
equipped with (connector type)		CORE
EN 13204		AS41/725-14.5
NFPA 1936		✓
max. working pressure	bar/Mpa	720 / 72
spreading distance	mm	725
max. spreading force	kN/t	280 / 28.6
min. spreading force (EN 13204)	kN/t	41 / 4.2
max. spreading force (NFPA 1936, HSF)	kN/t	70 / 7.1
min. spreading force (NFPA 1936, LSF)	kN/t	38 / 3.9
max. squeezing force	kN/t	59 / 6
pulling distance	mm	610
max. pulling force	kN/t	47 / 4.8
max. pulling force (NFPA 1936, HPF)	kN/t	47 / 4.8
min. pulling force (NFPA 1936, LPF)	kN/t	25 / 2.5
weight, ready for use	kg	14.5
dimensions (L x W x H)	mm	815 x 286 x 217
required oil content	cc	226
temperature range	°C	-20 – +55
built-in Speed Valve		✓
carrying handle lighting (6 LEDs)		✓



Accessories		Art. No.
1	cutting tips, set	150.006.474
2	pulling attachments, set	150.182.274
3	accessories, set in case (2 cutting tips, 2 spreading tips, 2 pulling attachments)	150.182.288
4	pulling chains, set	150.582.152
5	pulling chains, set in case	150.582.021



Holmatro spreader SP 5250



- Weight 15.9 kg
- Relevant spreading force* 51 kN / 5.2 t
- Spreading distance 725 mm

* this is the minimum spreading force you will always have at your disposal, measured at the top of the spreading tips over the full spreading distance

Specifications		SP 5250
article number		150.012.324
equipped with (connector type)		CORE
EN 13204		AS51/725-15.9
NFPA 1936		✓
max. working pressure	bar/Mpa	720 / 72
spreading distance	mm	725
max. spreading force	kN/t	366 / 37.3
min. spreading force (EN 13204)	kN/t	51 / 5.2
max. spreading force (NFPA 1936, HSF)	kN/t	97 / 9.9
min. spreading force (NFPA 1936, LSF)	kN/t	46 / 4.7
max. squeezing force	kN/t	135 / 13.8
pulling distance	mm	610
max. pulling force	kN/t	67 / 6.8
max. pulling force (NFPA 1936, HPF)	kN/t	67 / 6.8
min. pulling force (NFPA 1936, LPF)	kN/t	31 / 3.2
weight, ready for use	kg	15.9
dimensions (L x W x H)	mm	826 x 285 x 215
required oil content	cc	291
temperature range	°C	-20 – +55
built-in Speed Valve		✓
carrying handle lighting (6 LEDs)		✓



Accessories		Art. No.
1	cutting tips, set	150.006.474
2	pulling attachments, set	150.182.274
3	accessories, set in case (2 cutting tips, 2 spreading tips, 2 pulling attachments)	150.182.288
4	pulling chains, set	150.582.152
5	pulling chains, set in case	150.582.021



Holmatro spreader SP 5260



- Weight 19.6 kg
- Relevant spreading force* 62 kN / 6.3 t
- Spreading distance 822 mm

* this is the minimum spreading force you will always have at your disposal, measured at the top of the spreading tips over the full spreading distance

Specifications		SP 5260
article number		150.012.325
equipped with (connector type)		CORE
EN 13204		BS62/822-19.6
NFPA 1936		✓
max. working pressure	bar/Mpa	720 / 72
spreading distance	mm	822
max. spreading force	kN/t	522 / 53.2
min. spreading force (EN 13204)	kN/t	62 / 6.3
max. spreading force (NFPA 1936, HSF)	kN/t	117 / 11.9
min. spreading force (NFPA 1936, LSF)	kN/t	58 / 5.9
max. squeezing force	kN/t	127 / 13
pulling distance	mm	701
max. pulling force	kN/t	82 / 8.4
max. pulling force (NFPA 1936, HPF)	kN/t	82 / 8.4
min. pulling force (NFPA 1936, LPF)	kN/t	37 / 3.8
weight, ready for use	kg	19.6
dimensions (L x W x H)	mm	900 x 322 x 223
required oil content	cc	384
temperature range	°C	-20 – +55
built-in Speed Valve		✓
carrying handle lighting (6 LEDs)		✓



Accessories		Art. No.
1	cutting tips, set	150.006.466
2	pulling attachments, set	150.182.275
3	accessories, set in case (2 cutting tips, 2 spreading tips, 2 pulling attachments)	150.182.290
4	pulling chains, set	150.582.261
5	pulling chains, set in case	150.582.020



Holmatro spreader SP 5280



- Weight 19.4 kg
- Relevant spreading force* 83 kN / 8.5 t
- Spreading distance 663 mm

* this is the minimum spreading force you will always have at your disposal, measured at the top of the spreading tips over the full spreading distance

Specifications		SP 5280
article number		150.012.326
equipped with (connector type)		CORE
EN 13204		CS83/662-19.4
NFPA 1936		✓
max. working pressure	bar/Mpa	720 / 72
spreading distance	mm	662
max. spreading force	kN/t	463 / 47.2
min. spreading force (EN 13204)	kN/t	83 / 8.5
max. spreading force (NFPA 1936, HSF)	kN/t	142 / 14.5
min. spreading force (NFPA 1936, LSF)	kN/t	74 / 7.5
max. squeezing force	kN/t	159 / 16.2
pulling distance	mm	538
max. pulling force	kN/t	99 / 10.1
max. pulling force (NFPA 1936, HPF)	kN/t	99 / 10.1
min. pulling force (NFPA 1936, LPF)	kN/t	53 / 5.4
weight, ready for use	kg	19.4
dimensions (L x W x H)	mm	801 x 322 x 220
required oil content	cc	384
temperature range	°C	-20 – +55
built-in Speed Valve		✓
carrying handle lighting (6 LEDs)		✓



Accessories		Art. No.
1	cutting tips, set	150.006.466
2	pulling attachments, set	150.182.275
3	accessories, set in case (2 cutting tips, 2 spreading tips, 2 pulling attachments)	150.182.290
4	pulling chains, set	150.582.261
5	pulling chains, set in case	150.582.020

User, victim and environmentally friendly with excellent performance: introducing the battery powered Greenline EVO 3 range from Holmatro. Four models are available from the new 5000 series spreaders. Your benefits:

Optimum freedom of movement

Greenline EVO 3 models are self-contained and not connected to a pump. So they offer true optimum freedom of movement.

Use in all weather conditions

Suitable for use in all weather conditions, also in the case of (extreme) precipitation and temperatures down to -20° C.

Emission-free

No emissions, so healthier for rescuers and victims. Also ideal for use in confined and/or underground spaces.

Battery on top of tool

The battery has been positioned on the tool in such a way that exchanging it is quick and easy, even in confined spaces.

Advanced battery technology

Lithium-ion technology combines a long battery life with high capacity for maximum operational use.

Higher speed

Increased tool speed at a lower weight and noise level thanks to new and improved drive unit!



Holmatro Greenline EVO 3 battery range

Zero emissions, 100% performance

New battery: 20% more capacity. Work longer on one battery!



Holmatro spreader GSP 5240 CL EVO 3

- Weight incl. battery 15.4 kg
- Relevant spreading force* 40 kN / 4.1 t
- Spreading distance 510 mm

Holmatro spreader GSP 5240 EVO 3

- Weight incl. battery 20.3 kg
- Relevant spreading force* 41 kN / 4.2 t
- Spreading distance 725 mm

Holmatro spreader GSP 5250 EVO 3

- Weight incl. battery 21.7 kg
- Relevant spreading force* 51 kN / 5.2 t
- Spreading distance 725 mm

Holmatro spreader GSP 5260 EVO 3

- Weight incl. battery 25.7 kg
- Relevant spreading force* 62 kN / 6.3 t
- Spreading distance 822 mm

* this is the minimum spreading force you will always have at your disposal, measured at the top of the spreading tips over the full spreading distance

Specifications		GSP 5240 CL EVO 3	GSP 5240 EVO 3	GSP 5250 EVO 3	GSP 5260 EVO 3
article number		150.052.116	150.052.117	150.052.118	151.000.164
operator type		battery	battery	battery	battery
EN 13204 **		✓	✓	✓	✓
NFPA 1936		✓	✓	✓	✓
max. working pressure	bar/Mpa	720 / 72	720 / 72	720 / 72	720 / 72
spreading distance	mm	510	725	725	822
max. spreading force	kN/t	131 / 13.4	280 / 28.6	366 / 37.3	522 / 53.2
min. spreading force (EN 13204)	kN/t	40 / 4.1	41 / 4.2	51 / 5.2	62 / 6.3
max. spreading force (NFPA 1936, HSF)	kN/t	53 / 5.4	70 / 7.1	97 / 9.9	117 / 11.9
min. spreading force (NFPA 1936, LSF)	kN/t	35 / 3.6	38 / 3.9	46 / 4.7	58 / 5.9
max. squeezing force	kN/t	47 / 4.8	59 / 6	135 / 13.8	127 / 13
pulling distance	mm	393	610	610	701
max. pulling force	kN/t	47 / 4.8	47 / 4.8	67 / 6.8	82 / 8.4
max. pulling force (NFPA 1936, HPF)	kN/t	47 / 4.8	47 / 4.8	67 / 6.8	82 / 8.4
min. pulling force (NFPA 1936, LPF)	kN/t	24 / 2.4	25 / 2.5	31 / 3.2	37 / 3.8
weight, incl. battery	kg	15.4	20.3	21.7	25.7
weight, excl. battery	kg	14.4	19.3	20.7	24.7
dimensions (L x W x H)	mm	819 x 277 x 205	952 x 286 x 216	964 x 286 x 216	1037 x 322 x 223
temperature range	°C	-20 – +55	-20 – +55	-20 – +55	-20 – +55
carrying handle lighting (6 LEDs)		✓	✓	✓	✓

** Battery-operated hydraulic rescue equipment falls outside the scope of the EN 13204 standard. However, the models mentioned on this page have been tested according to this standard and found compliant with all relevant requirements.

Holmatro Greenline EVO 3 accessories

Everything you might need for your Greenline EVO 3 spreaders

Required Accessories (for all models)			Art. No.
1	battery BPA 286 (6.0 Ah)		151.000.307
Accessories (for all models)			Art. No.
2	battery charger BCH1 (220 - 240 VAC)		150.182.208
	battery charger BCH2 (100 - 120 VAC)		150.182.209
	battery car charger BCH3, 12-24 VDC		150.182.286
3	mains power connector BMC1 (220 - 240 VAC) *		150.182.206
	mains power connector BMC2 (100 - 120 VAC) *		150.182.207
4	battery pouch		150.182.214
5	carrying strap		150.182.249
Accessories		For model	Art. No.
6	pulling attachment set PAS 01	GSP 5240 CL EVO 3	150.182.273
	pulling attachment set PAS 02	GSP 5240 EVO 3 GSP 5250 EVO 3	150.182.274
	pulling attachment set PAS 03	GSP 5260 EVO 3	150.182.275
7	pulling chain set PCS 01	GSP 5240 CL EVO 3 GSP 5240 EVO 3 GSP 5250 EVO 3	150.582.152
	pulling chain set PCS 03	GSP 5260 EVO 3	150.582.261
8	pulling chain set in case PCS 02	GSP 5240 CL EVO 3 GSP 5240 EVO 3 GSP 5250 EVO 3	150.582.021
	pulling chain set in case PCS 04	GSP 5260 EVO 3	150.582.020
9	cutting tip set CTS 01	GSP 5240 EVO 3 GSP 5250 EVO 3	150.006.474
	cutting tip set CTS 02	GSP 5260 EVO 3	150.006.466
10a	accessories set in case ACS 01 (2 spreading tips, 2 pulling attachments)	GSP 5240 CL EVO 3	150.182.289
10b	accessory set in case ACS 02 (2 cutting tips, 2 spreading tips, 2 pulling attachments)	GSP 5240 EVO 3 GSP 5250 EVO 3	150.182.288
	accessory set in case ACS 03 (2 cutting tips, 2 spreading tips, 2 pulling attachments)	GSP 5260 EVO 3	150.182.290

* Mains cable length: 2.5 m, tool cable length: 8 m



The new Holmatro 5000 series spreaders

The complete range



Specifications		SP 5240 CL	SP 5240	SP 5250	SP 5260	SP 5280
article number		150.012.322	150.012.323	150.012.324	150.012.325	150.012.326
equipped with (connector type)		CORE	CORE	CORE	CORE	CORE
EN 13204		✓ *	AS41/725-14.5	AS51/725-15.9	BS62/822-19.6	CS83/662-19.4
NFPA 1936		✓	✓	✓	✓	✓
max. working pressure	bar/Mpa	720 / 72	720 / 72	720 / 72	720 / 72	720 / 72
spreading distance	mm	510	725	725	822	662
max. spreading force	kN/t	131 / 13.4	280 / 28.6	366 / 37.3	522 / 53.2	463 / 47.2
min. spreading force (EN 13204)	kN/t	40 / 4.1	41 / 4.2	51 / 5.2	62 / 6.3	83 / 8.5
max. spreading force (NFPA 1936, HSF)	kN/t	53 / 5.4	70 / 7.1	97 / 9.9	117 / 11.9	142 / 14.5
min. spreading force (NFPA 1936, LSF)	kN/t	35 / 3.6	38 / 3.9	46 / 4.7	58 / 5.9	74 / 7.5
max. squeezing force	kN/t	47 / 4.8	59 / 6	135 / 13.8	127 / 13	159 / 16.2
pulling distance	mm	393	610	610	701	538
max. pulling force	kN/t	47 / 4.8	47 / 4.8	67 / 6.8	82 / 8.4	99 / 10.1
max. pulling force (NFPA 1936, HPF)	kN/t	47 / 4.8	47 / 4.8	67 / 6.8	82 / 8.4	99 / 10.1
min. pulling force (NFPA 1936, LPF)	kN/t	24 / 2.4	25 / 2.5	31 / 3.2	37 / 3.8	53 / 5.4
weight, ready for use	kg	9.6	14.5	15.9	19.6	19.4
dimensions (L x W x H)	mm	685 x 274 x 207	815 x 286 x 217	826 x 285 x 215	900 x 322 x 223	801 x 322 x 220
required oil content	cc	124	226	291	384	384
temperature range	°C	-20 - +55	-20 - +55	-20 - +55	-20 - +55	-20 - +55
built-in Speed Valve		✓	✓	✓	✓	✓
carrying handle lighting (6 LEDs)		✓	✓	✓	✓	✓
also available with Greenline battery		✓	✓	✓		

* EN 13204 compliant, except for spreading distance

About Holmatro

For half a century, Holmatro has been developing, producing and testing high-pressure hydraulic equipment for industrial, rescue and special tactics applications. Based on the needs of users, our products are known for their high quality and innovative technology. Holmatro sells and services these products through offices in various countries and an extensive dealer network.

When it comes to Holmatro rescue equipment, our highly experienced engineers translate innovative ideas into lighter, more powerful solutions for fire and rescue departments. The result is a full range of high-quality tools that enable you to work efficiently under pressure. With Holmatro it's safer, easier and quicker to save lives.

Holmatro products are manufactured in the Netherlands and the USA at our state-of-the-art production facilities. Innovation, quality and service are at the heart of our company philosophy. Thanks to an extensive range of services including maintenance and training, our products last for years. That's why they are the tools of choice for rescue workers throughout the world. Once you use them, you'll use them for life.

Disclaimer

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. N.V. Holmatro and its affiliated companies (here-after: Holmatro) cannot be held liable in any way for the consequences of activities undertaken based on this printed matter. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (phone number: +31 (0)162-589200). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.



YOU CAN COUNT ON US, FOR LIFE

holmatro.com

 Holmatro Rescue World

 @HolmatroRescue

 holmatrorescue

 HolmatroRescue